



SF450 FOLD-OUT DOUBLE STEP



Step Operation

The SF450 manual step is deployed standing outside the vehicle and simply pulling on the grab handle to swing the step out through the doorway and lower it to its fully deployed position. It is stowed again from standing outside the vehicle and lifting the grab handle to fold it back through the doorway until it is fully folded and retained by the anti-rattle spring clips.

Standard Equipment

Extruded Anodised Aluminium ribbed tread profile
Extruded Anodised Aluminium Side arms and links
Nylon pivot bearings
Rubber tiger strip to top tread
Grab handle
Floor mounting plates

Dimensions

Tread Width: 450mm
Tread Height below floor mounting height: 240mm
Minimum step well width to mount step: 575mm
Minimum step well depth to mount step: 185mm


Warranty

12 months on site with option at time of purchase to increase for a further year subject to approved service and maintenance.
Complies with all current legislative requirements.
CE marked.

The company has a policy of continual improvement and reserves the right to change the product specifications without notice

Weight

12.15 kgs

 44(0)1270-874982

Stayco is the registered trade mark and brand name of W.S.H.Taylor Engineering Ltd | Units 36 - 39 Building 10, Radway Industrial Park, Radway Green, Crewe, Cheshire, CW2 5PR | Tel: 44(0)1270-874982, Fax: 44(0)1270-886155