







Standard Equipment

Extruded Anodised Aluminium ribbed tread profile High grip Yellow and Black Rubber Strip to tread top edge

Soft Rubber Cushion Strip to leading edge of tread Extruded Anodised Aluminium Side arms Rubber Weather Flap to underside of Tread High visibility corner mouldings Damped gas spring Galvanised Steel Case Stainless Steel Rails Nylon Rollers Over-centre latch mechanism

Options

Limit switch

Corner Tread Flashing Lights
Under Tread Lights
Vehicle Mounting Kits for suitable vehicles
Wire loom kit consisting of:
Wire loom
Control Unit
Dash switch
Dash warning light

Patented deployed lock-out mechanism

Step Operation

The WM600 manual cassette step is deployed by a damped gas spring which is activated by simply pushing the tread edge in a small distance with your foot and releasing. Once deployed, the tread is automatically locked in that position by a patented catch system which is activated by the weight of the person standing on the tread. The step is simply stowed by pushing the tread fully in by foot until the over-centre latch engages. There are no vulnerable release pedals required to operate the step.

Dimensions

Tread size deployed: 260mm x 610mm Tread edge from sill lip deployed: 315mm Tread deployment movement: 205mm

Minimum projection of case below sill height: 68mm

Case depth behind sill lip: 365mm*

Closed tread projection out from sill lip: 110mm*

Overall width of case: 688mm

*Can be varied - depending on mounting brackets used

Weight

17kgs

Warranty

12 months on site with option at time of purchase to increase for a further year subject to approved service and maintenance.

Complies with all current legislative requirements. CE marked.

The Company has a policy of continual improvement and reserves the right to change the product specifications without notice



44(0)1270-874982