



DL600S FOLD-OUT DOUBLE STEP



Step Operation

The DL600S is deployed standing outside the vehicle and simply pulling on the grab handle to swing the step out through the doorway and lower it to its fully deployed position. It is stowed again from standing outside the vehicle and lifting the grab handle to fold it back through the doorway until it is fully folded and retained by the anti-rattle spring clips. The weight of the step is counterbalanced by the tension springs mounted each side of the step unit.

Dimensions

Tread width: 610mm
Step heights: Top to Mid Step: 156mm
Step heights: Mid to Lower Step: 160mm

Weight

17kgs

Standard Equipment

Extruded Anodised Aluminium ribbed tread profile
Extruded Anodised Aluminium Side arms and links
Nylon pivot bearings
Rubber tiger strip to top tread
Grab handle
Assist springs
Floor mounting plates

Options

Handrail Kit

Warranty

12 months on site
Complies with all current legislative requirements.
CE marked.

The Company has a policy of continual improvement and reserves the right to change the product specifications without notice

 44(0)1270-874982

Stayco is the registered trade mark and brand name of W.S.H.Taylor Engineering Ltd | Units 36 - 39 Building 10, Radway Industrial Park, Radway Green, Crewe, Cheshire, CW2 5PR | Tel: 44(0)1270-874982, Fax: 44(0)1270-886155