



## SF600 FOLD-OUT DOUBLE STEP



### Step Operation

---

The SF600 manual step is deployed standing outside the vehicle and simply pulling on the grab handle to swing the step out through the doorway and lower it to its fully deployed position. It is stowed again from standing outside the vehicle and lifting the grab handle to fold it back through the doorway until it is fully folded and retained by the anti-rattle spring clips.

### Standard Equipment

---

Extruded Anodised Aluminium ribbed tread profile  
Extruded Anodised Aluminium Side arms and links  
Nylon pivot bearings  
Rubber tiger strip to top tread  
Grab handle  
Floor mounting plates

### Dimensions

---

Tread Width: 610mm  
Tread Height below floor mounting height: 240mm  
Minimum step well width to mount step: 735mm  
Minimum step well depth to mount step: 185mm

### Warranty

---

12 months on site with option at time of purchase to increase for a further year subject to approved service and maintenance.

Complies with all current legislative requirements.  
CE marked.

The company has a policy of continual improvement and reserves the right to change the product specifications without notice

### Weight

---

12.9 kgs

44(0)1270-874982

Stayco is the registered trade mark and brand name of W.S.H.Taylor Engineering Ltd | Units 36 - 39 Building 10, Radway Industrial Park, Radway Green, Crewe, Cheshire, CW2 5PR | Tel: 44(0)1270-874982, Fax: 44(0)1270-886155